



ABF Motorbike Oils

We redefined lubrication through ABF technology
Setting the standards in Effectiveness of The Lubricant



ABF-ECI M7 4T Gordon

BORN FOR HI-PERFORMANCE

Produce of Singapore

Updated 2015JUL09

ABF-ECI M7 4T Gordon is a premium quality synthetic based lubricant developed for use in all types of 4-stroke motorcycles. It is formulated from premium quality base stocks and enhanced with Steel Shield ABF Technology to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles. The oils provide excellent protection towards engine, gearbox and wet clutches used in 4-stroke motorcycles and ensures the highest possible reliability even under the most harsh driving environment.

ABF-ECI M7 4T Gordon sets a New Standard in lubrication !

Excellent resistance of the oil film at High Temperatures.
Superior thermo-oxidative stability, minimizing" deposits and sludge formation.
Exceptional anti-wear properties protect vital engine and gear components .
Controlled frictional properties eliminate clutch slippage improving drivability.
Ensures complete wear protection at start up at low amperage draw on your battery.
Increased output power.
Reduced downtime and maintenance cost.
Highly recommended for a wide range of 4-stroke motorcycles.

API SM JASO MA/MA2

TYPICAL CHARACTERISTICS

SAE Grade			10w50
Viscosity grade	kg/m ³		870
Viscosity @ 40 °C	cSt	ASTM D445	120
Viscosity @ 100 °C	cSt	ASTM D445	18.0
Viscosity Index		ASTM D2270	165
Pour Point	°C	ASTM D97	-48
Flash Point COC	°C	ASTM D92	≥237
Mass Density @ 15°C	kg/l		0.855

Remarks : Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model, year and environment of operation.

STEEL SHIELD TECHNOLOGIES

809B, 8/F., Block B, Goodview Industrial Building, 11 Kin Fat Street, Tuen Mun, N.T., HK

Tel:(852) 2545 8029 Fax: (852) 2545 8030

Website: www.steelshieldtech.com.hk Facebook: www.facebook.com/steelshieldtech