



SST Motorbike Oils

We redefined lubrication through ABF technology
Setting the standards in Effectiveness of The Lubricant



SST-Basic 4T 10W40

EXCELLENT LUBRICATION

Produce of Singapore

Updated 2014DEC29

SST-Basic are premium four stroke motorcycle gasoline engine oils. The oils possess high friction durability, superior shear stability for gearboxes protection. They meet performance requirements of all types of 4T motorcycle gasoline engines made by Japanese OEM such as Honda, Yamaha, Suzuki, etc.

API SM/SL/SJ/SG JASO T903:2006, JASO MA-2

- Enhanced friction durability, optimizes clutch performance
- Superior engine cleanliness
- Outstanding wear and corrosion protection
- Excellent oxidation, thermal stability
- Extend oil drain interval
- Prolong engine life
- Minimize maintenance costs

TYPICAL CHARACTERISTICS

SAE Grade			10W40	15w40
Viscosity @ 40 °C	cSt	ASTM D445	112	89
Viscosity @ 100 °C	cSt	ASTM D445	15.8	15.7
Viscosity Index		ASTM D2270	150	138
Pour Point	°C	ASTM D97	-30	-25
Flash Point COC	°C	ASTM D92	≥217	≥219
Sulfated Ash	%	JIS K2272	0.81	0.81
Mass Density @ 15°C	kg/l		0.865	0.865

Remarks : Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model, year and environment of operation.

STEEL SHIELD TECHNOLOGIES

809B, 8/F., Block B, Goodview Industrial Building, 11 Kin Fat Street, Tuen Mun, N.T., HK

Tel:(852) 2545 8029 Fax: (852) 2545 8030

Website: www.steelshieldtech.com.hk Facebook: www.facebook.com/steelshieldtech