



SST Motorbike Oils

We redefined lubrication through ABF technology
Setting the standards in Effectiveness of The Lubricant



SST-Basic 4T 5W40

BORN FOR PERFORMANCE

Produce of Singapore

Updated 2014DEC29

SST-Basic 4T is a premium quality fully synthetic lubricant especially developed for use in high powered 4-stroke motorcycles. It is formulated from premium quality base stocks to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles. The oils provide excellent protection towards engine, gearbox and wet clutches used in 4-stroke motorcycles and ensures the highest possible reliability even under the most severe operating conditions.

Superior thermo-oxidative stability, minimizing" deposits and sludge formation
Exceptional anti-wear properties protect vital engine and gear components
Controlled frictional properties eliminate clutch slippage improving driveability
Ensures complete wear protection at start up under low ambient temperatures
Minimize maintenance cost
Highly recommended for a wide range of high powered 4-stroke motorcycles

API SJ/SL JASO MA/MA2

TYPICAL CHARACTERISTICS

SAE Grade			5W40	5w50
Viscosity @ 40 °C	cSt	ASTM D445	90	127
Viscosity @ 100 °C	cSt	ASTM D445	14.2	19.3
Viscosity Index		ASTM D2270	160	173
Pour Point	°C	ASTM D97	-39	-45
Flash Point COC	°C	ASTM D92	≥200	≥222
Mass Density @ 15°C	kg/l		0.85	0.855

Remarks : Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model, year and environment of operation.

STEEL SHIELD TECHNOLOGIES

809B, 8/F., Block B, Goodview Industrial Building, 11 Kin Fat Street, Tuen Mun, N.T., HK

Tel:(852) 2545 8029 Fax: (852) 2545 8030

Website: www.steelshieldtech.com.hk Facebook: www.facebook.com/steelshieldtech