



SST-ECI AIR-COMPRESSOR LA 0.5 OILS

DESCRIPTION

SST-ECI LA 0.5 are air compressor oils blended with highly refined mineral base oils together with Steel Shield ABF advanced technology additives. The oils reduce internal friction, protect metal parts, exhibit good oxidation stability, excellent rust and corrosion protection and demulsification properties, meet the requirements of DIN 51506 VD-L

BENEFITS

- Good anti-oxidation and anti-rust properties
- Excellent thermal stability
- Resistance to sludge deposit
- Excellent chemical stability
- Excellent demulsifiability
- Improve efficiency
- Energy Saving average 5~12%
- Extend the life of all metal parts
- Extend oil change interval
- Reduce noise
- Less downtime and save maintenance cost

APPLICATION

AP COMPRESSO are recommended for the lubricating of rotary sliding vane, screw air compressors as well as reciprocating air compressors.

TYPICAL SPECIFICATION

ISO Grade		32	46	68	100	150
Kinematic Viscosity,						
@ 40°C, cSt	ASTM D445	29	46	68	97	150
@ 100°C, cSt	ASTM D445	5.4	6.8	8.5	11.0	14.8
Viscosity Index	ASTM D2270	108	105	97	97	97
Flash Point (COC), °C	ASTM D92	215	220	230	245	248
Pour Point, °C	ASTM D97	-15	-12	-10	-10	-9

Remarks : Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model, year and environment of operation.

STEEL SHIELD TECHNOLOGIES

809B, 8/F., Block B, Goodview Industrial Building, 11 Kin Fat Street, Tuen Mun, N.T., HK

Tel:(852) 2545 8029 Fax: (852) 2545 8030

Website: www.steelshieldtech.com.hk Facebook: www.facebook.com/steelshieldtech