



Steel Shield Motor Oils

We redefined lubrication through ABF technology
Setting the standards in Effectiveness of The Lubricant



Steel Shield ZAGATO GT made for Racing

Specifically designed for competition engines

Produce of USA

Updated 2014DEC29

ZAGATO GT is designed for use in high-performance, high horsepower competition engines. Formulated with Steel Shield unique formula ABF Technology, Group II base oils, and shear stable viscosity modifiers, ZAGATO GT is made for Racing. It provides superior protection against wear and thermal breakdown under high loads and high operating temperatures experienced in racing engines.

ZAGATO GT is recommended for supercharged, turbocharged and naturally aspirated competition engines utilizing racing gasoline, diesel fuel, methanol or nitromethane fuels.

ZAGATO GT also provides excellent protection in high-performance motorcycles and ATVs.

TYPICAL CHARACTERISTICS

Viscosity Grade	15W-40	20W-50
Viscosity @ 100°C, cSt	15.3	20.5
Viscosity @ 40°C, cSt	111	172.0
Viscosity Index (Min.)	148	135
Flash Point °F / °C	425 / 218	464 / 240
Pour Point °F / °C	-25 / -32	-17 / -27
Gravity, Degrees API	32.0	28.3
Phosphorus, ppm	1200	1200
Zinc, ppm	1300	1300

Remarks : Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model, year and environment of operation.

STEEL SHIELD TECHNOLOGIES

809B, 8/F., Block B, Goodview Industrial Building, 11 Kin Fat Street, Tuen Mun, N.T., HK

Tel:(852) 2545 8029 Fax: (852) 2545 8030

Website: www.steelshieldtech.com.hk Facebook: www.facebook.com/steelshieldtech